



DISTANCE BETWEEN SUPPORTS

MESH TYPE mm x mm	THICKNESS mm		DISTANCE BETWEEN SUPPORTS							
			400 mm	500 mm	600 mm	800 mm	1000 mm	1200 mm	1400 mm	1500 mm
100 x 25	25	C	1340	860	600	340	220	150	110	100
		d	4	5	6	8	10	12	14	15
40 x 40	25	C	850	550	380	220	140	100	70	60
		d	4	5	6	8	10	12	14	15
40 x 40	30	C	1540	1000	700	390	250	180	130	110
		d	4	5	6	8	10	12	14	15
8 x 8	30	C	1900	1230	860	490	310	220	160	140
		d	4	5	6	8	10	12	14	15
19 x 19	30	C	1610	1040	730	410	270	180	140	120
		d	4	5	6	8	10	12	14	15
40 x 40	38	C	3000	1950	1360	770	500	350	250	220
		d	4	5	6	8	10	12	14	15
19 x 19	40	C	3560	2320	1630	930	600	420	310	270
		d	4	5	6	8	10	12	14	15
50 x 50	50	C	5480	3590	2530	1440	930	650	480	420
		d	4	5	6	8	10	12	14	15
19 x 19	50	C	7090	4680	3300	1890	1220	850	630	550
		d	4	5	6	8	10	12	14	15
25 x 50	55	C	9760	6470	4580	2630	1700	1180	870	760
		d	4	5	6	8	10	12	14	15
38 x 38	63	C	20850	13840	9810	5630	3640	2540	1870	1630
		d	4	5	6	8	10	12	14	15



C = Concentrated Line load kg/m

d = Deflection of corresponding load (expressed in mm)

The load values refer to a L/100 (1%) deflection

The load values indicated represent average values (tolerance +/- 15%)